State of California AIR RESOURCES BOARD

EXECUTIVE ORDER U-R-4-45

Relating to Certification of New Heavy-Duty Off-Road Equipment Engines

DEERE POWER SYSTEMS GROUP OF DEERE & COMPANY

Pursuant to the authority vested in the Air Resources Board by Sections 43000.5, 43013 and 43018 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following Deere Power Systems Group of Deere & Company 1999 model-year engine, with rated power between 175 and 750 horsepower, and exhaust emission control systems are certified as described below for use in heavy-duty off-road equipment:

Typical Equipment Usage:

Dozer and Other OEM Products

Fuel Type: Diesel

Engine Family	Displacement <u>Liters Cubic Inches</u>	Exhaust Emission Control Systems and Special Features
XJDXL06.8015 (350TB)	6.8/4.5 415/275	Turbocharger

Engine models and codes are listed on attachments. Production engines shall be in all material respects the same as those for which certification is granted.

The total hydrocarbons (THC), carbon monoxide (CO), nitrogen oxides (NOx), and particulate matters (PM) certification exhaust emission standards, in grams per brake horsepower-hour (g/bhp-hr), and the opacity of smoke emission standards, in percent (%), during acceleration (Accel), lugging (Lug), and peak (Peak) modes, for this engine family are (Title 13, California Code of Regulations, Section 2423):

Exhaust Emissions (g/bhp-hr)			Smoke	Smoke Opacity (%)			
<u>THC</u>	<u>CO</u> _	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	Lug	<u>Peak</u>	
1.0	8.5	6.9	0.4	20	15	50	

DEERE POWER SYSTEMS GROUP OF DEERE & COMPANY EXECUTIVE ORDER U-R-4-45 (Page 2 of 2)

The THC, CO, NOx and PM exhaust emission certification values, in g/bhp-hr, and the opacity of smoke emission certification values, in percent (%), for this engine family are:

	<u>Exhaust</u>	<u>Emissio</u>	u (d/pj	np-hr)	_ Smoke (pacity	(%)
Engine Family	THC	<u>co</u>	<u>NOx</u>	<u>PM</u>	<u>Accel</u>	Lug	<u>Peak</u>
XJDXL06.8015 (350TB)	0.2	0.8	5.5	0.2	10	8	24

BE IT FURTHER RESOLVED: That the listed engine models comply with the "Exhaust Emission Standards and Test Procedures -- Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2423) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the listed engine models also comply with the "Emission Control Labels -- 1996 and Later Heavy-Duty Off-Road Diesel Cycle Engines" (Title 13, California Code of Regulations, Section 2424) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2425 et seq.).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Executed at El Monte, California this ______day of January 1999.

R/B. Summerfield, Chief Mobile Source Operations Division

Engine Model Summary Form

Manufacturer:

Deere Power Systems Group of Deere & Company

Engine category:

Nonroad Over 50 Hp

EPA Engine Family: XJDXL06.8015

Mfr Family Name: 350TB

Process Code:

New Submission

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
6068TF250A	6068T	194@2400	93@2400	74@2400	509@1400	107@1400	19@1400	EM TC
4045TT055	4045T	109@2300	80@2300	41@2300	303@1400	93@1400	29@1400	EM, TC
4045TF250	4045T	125@2400	89@2400	47@2400	308@1400	101@1400	31@1400	EM, TC
6068TT051	6068T	148@2150	73@2150	52@2150	432@1400	85@1400	39@1400	EM, TC
6068TDW52	6068T	157@2200	79@2200	57.3@2200	496@1400	102@1400	47.4@1400	EM, TC
6068TDW55	6068T	157@2200	79@2200	57.3@2200	496@1400	102@1400	47.4@1400	EM, TC
6068TT053	6068T	161@2200	80@2200	58@2200	499@1400	101@1400	47@1400	EM, TC
6068TF250B	6068T	185@2400	89@2400	71@2400	503@1400	103@1400	19@1400	EM, TC
4045TT052	4045T	93@2200	69@2200	33.5@2200	272@1200	81@1200	21.5@1200	EM, TC
	ender en							